

TOSHIBA

Intelligent Surveillance. Built to Perform.

Delivering a smart video storage solution with enhanced reliability and performance that are optimized for 24/7 advanced AI-enabled network video recorders and video analytics servers.



S300 AI Surveillance Internal Hard Drive

The Toshiba S300 AI Surveillance Hard Drive is built for AI-driven surveillance and video analytics. Powered by Toshiba's OptiFrame™ Technology, it delivers smooth multi-stream performance, efficient data handling, and reduced frame loss even under heavy workloads.

Designed for 24/7 operation⁶, the S300 AI supports up to 64 HD camera streams⁴ and 32 AI streams, with capacities up to 24TB¹ for extended video retention. It offers Enterprise-level reliability with up to 550TB/year workload rate⁹ and up to 2.5 million hours MTBF⁸ to handle workload-intensive AI analytics.

With 7,200 RPM speed, up to 1GB cache, and CMR recording technology, the S300 AI delivers fast, reliable performance with advanced caching and enhanced random write operation for real-time AI data capture.



Image does not represent actual product.

TOSHIBA

S300 AI Surveillance Internal Hard Drive

Application¹³

- Surveillance Network Video Recorders (sNVR)
- Surveillance Digital Video Recorders (sDVR)
- RAID Storage Arrays for Surveillance
- Advanced AI-powered Video Recorders
- Video Analytics Servers



Product image may represent a design model.



Enterprise-level Reliability

Built for 24/7 operation⁶ with up to 550TB/year workload rate⁹ and up to 2.5M hours MTBF⁸ for reliable performance in workload-heavy AI environments.



Optimized for Multi-Bay, Multi-Stream Setups

Supports up to 64 HD cameras⁴ and 32 AI streams, with built-in RV sensors to minimize vibrations and ensure stable operation in multi-bay systems.



Advanced Performance

7,200 RPM, up to 1GB cache, and CMR technology deliver fast, reliable data transfer with enhanced caching for seamless AI data capture and analytics.



Toshiba OptiFrame™ Technology

Smart firmware optimizes multi-stream data flow, reducing frame drops for smooth recording and playback.



AI-Ready Design

Optimized for high random write activity to support real-time AI analytics and uninterrupted insights.



Peace of Mind

Toshiba Five-year limited warranty¹⁰.



Capacity ¹	24TB	22TB	20TB
Model Number (Retail packaging)	HDWTB2EXZSTA	HDWTB2CXZSTA	HDWTB2AXZSTA
Model Number (Bulk)	MG11ACA24TE-V	MG11ACA22TE-V	MG11ACA20TE-V
Basic Specifications			
Recording Technology²	CMR	CMR	CMR
Interface	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s
Form Factor³	3.5-inch	3.5-inch	3.5-inch
Sector Size	512e	512e	512e
Features			
AI Streams	Up to 32	Up to 32	Up to 32
Firmware Technology	OptiFrame™ AI	OptiFrame™ AI	OptiFrame™ AI
Number of Cameras Supported⁴	Up to 64	Up to 64	Up to 64
Drive Bays Supported⁵	Up to 24	Up to 24	Up to 24
Tarnish Resistant	Yes	Yes	Yes
24 x 7 Operation⁶	Yes	Yes	Yes
Rotational Vibration (RV) Sensors	Yes	Yes	Yes
Shock Sensor	Yes	Yes	Yes
Performance			
Rotational Speed [RPM]	7,200	7,200	7,200
Max Data Transfer Speed⁷ [MB/s Typ.](Sustained)	309	299	295
Cache Size [MB]	1024	1024	1024
Reliability			
MTTF/MTBF [Hours] ⁸	2,500,000	2,500,000	2,500,000
Unrecoverable Error Rate	10 per 10 ¹⁶	10 per 10 ¹⁶	10 per 10 ¹⁶
Maximum Workload Rate [TB/Year] ⁹	550	550	550
Load/Unload Cycles	600,000	600,000	600,000
Limited Warranty¹⁰ [Years]	5	5	5
Power Management			
Supply Voltage	12 VDC ±10 % 5 VDC +10 % / -7 %	12 VDC ±10 % 5 VDC +10 % / -7 %	12 VDC ±10 % 5 VDC +10 % / -7 %
Power Consumption (Operating) [W]	8.11	8.11	8.11
Power Consumption (Active Idle) [W]	4.35	4.35	4.35
Environmental			
Temperature (Operating) ¹¹ [°C]	5 to 60 (surface)	5 to 60 (surface)	5 to 60 (surface)
Temperature (Non-Operating) [°C]	-40 to 70	-40 to 70	-40 to 70
Vibration (Operating) [m/s ²]	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)
Vibration (Non-Operating) [m/s ²]	29.4 {3.0 G} (5 to 500Hz)	29.4 {3.0 G} (5 to 500Hz)	29.4 {3.0 G} (5 to 500Hz)
Shock (Operating) [m/s ²]	490 {50 G} (2 ms duration)	490 {50 G} (2 ms duration)	490 {50 G} (2 ms duration)
Shock (Non-Operating) [m/s ²]	1,960 {200 G} (2 ms duration)	1,960 {200 G} (2 ms duration)	1,960 {200 G} (2 ms duration)
Acoustics Idle Mode [dB]	20	20	20
Physical			
Height [mm Max.]	26.1	26.1	26.1
Length [mm Max.]	147	147	147
Width [mm Max.]	101.85	101.85	101.85
Weight [g Max.]	730	730	730

Capacity ¹	18TB	16TB	14TB
Model Number (Retail packaging)	HDWTB1JXZSTA	HDWTB1GXZSTA	HDWTB1EXZSTA
Model Number (Bulk)	MG11ACA18TE-V	MG11ACA16TE-V	MG11ACA14TE-V
Basic Specifications			
Recording Technology²	CMR	CMR	CMR
Interface	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s
Form Factor³	3.5-inch	3.5-inch	3.5-inch
Sector Size	512e	512e	512e
Features			
AI Streams	Up to 32	Up to 32	Up to 32
Firmware Technology	OptiFrame™ AI	OptiFrame™ AI	OptiFrame™ AI
Number of Cameras Supported⁴	Up to 64	Up to 64	Up to 64
Drive Bays Supported⁵	Up to 24	Up to 24	Up to 24
Tarnish Resistant	Yes	Yes	Yes
24 x 7 Operation⁶	Yes	Yes	Yes
Rotational Vibration (RV) Sensors	Yes	Yes	Yes
Shock Sensor	Yes	Yes	Yes
Performance			
Rotational Speed [RPM]	7,200	7,200	7,200
Max Data Transfer Speed⁷ [MB/s Typ.](Sustained)	295	295	295
Cache Size [MB]	1024	1024	1024
Reliability			
MTTF/MTBF [Hours] ⁸	2,500,000	2,500,000	2,500,000
Unrecoverable Error Rate	10 per 10 ¹⁶	10 per 10 ¹⁶	10 per 10 ¹⁶
Maximum Workload Rate [TB/Year] ⁹	550	550	550
Load/Unload Cycles	600,000	600,000	600,000
Limited Warranty¹⁰ [Years]	5	5	5
Power Management			
Supply Voltage	12 VDC ±10 % 5 VDC +10 % / -7 %	12 VDC ±10 % 5 VDC +10 % / -7 %	12 VDC ±10 % 5 VDC +10 % / -7 %
Power Consumption (Operating) [W]	7.89	7.41	7.41
Power Consumption (Active Idle) [W]	4.16	3.66	3.66
Environmental			
Temperature (Operating) ¹¹ [°C]	5 to 60 (surface)	5 to 60 (surface)	5 to 60 (surface)
Temperature (Non-Operating) [°C]	-40 to 70	-40 to 70	-40 to 70
Vibration (Operating) [m/s ²]	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)
Vibration (Non-Operating) [m/s ²]	29.4 {3.0 G} (5 to 500Hz)	29.4 {3.0 G} (5 to 500Hz)	29.4 {3.0 G} (5 to 500Hz)
Shock (Operating) [m/s ²]	490 {50 G} (2 ms duration)	490 {50 G} (2 ms duration)	490 {50 G} (2 ms duration)
Shock (Non-Operating) [m/s ²]	1,960 {200 G} (2 ms duration)	1,960 {200 G} (2 ms duration)	1,960 {200 G} (2 ms duration)
Acoustics Idle Mode [dB]	20	20	20
Physical			
Height [mm Max.]	26.1	26.1	26.1
Length [mm Max.]	147	147	147
Width [mm Max.]	101.85	101.85	101.85
Weight [g Max.]	730	730	730

Capacity ¹	10TB	8TB
Model Number (Retail packaging)	HDWTA1AXZSTA	HDWTA80XZSTA
Model Number (Bulk)	MG10ADA10TE-V	MG10ADA800E-V
Basic Specifications		
Recording Technology²	CMR	CMR
Interface	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s
Form Factor³	3.5-inch	3.5-inch
Sector Size	512e	512e
Features		
AI Streams	Up to 32	Up to 32
Firmware Technology	OptiFrame™ AI	OptiFrame™ AI
Number of Cameras Supported⁴	Up to 64	Up to 64
Drive Bays Supported⁵	Up to 24	Up to 24
Tarnish Resistant	Yes	Yes
24 x 7 Operation⁶	Yes	Yes
Rotational Vibration (RV) Sensors	Yes	Yes
Shock Sensor	Yes	Yes
Performance		
Rotational Speed [RPM]	7,200	7,200
Max Data Transfer Speed⁷ [MB/s Typ.](Sustained)	281	281
Cache Size [MB]	512	512
Reliability		
MTTF/MTBF [Hours] ⁸	2,000,000	2,000,000
Unrecoverable Error Rate	10 per 10 ¹⁶	10 per 10 ¹⁶
Maximum Workload Rate [TB/Year] ⁹	550	550
Load/Unload Cycles	600,000	600,000
Limited Warranty¹⁰ [Years]	5	5
Power Management		
Supply Voltage	12 VDC ±10 % 5 VDC +10 % / -7 %	12 VDC ±10 % 5 VDC +10 % / -7 %
Power Consumption (Operating) [W]	9.63	9.63
Power Consumption (Active Idle) [W]	5.74	5.74
Environmental		
Temperature (Operating) ¹¹ [°C]	5 to 60 (surface)	5 to 60 (surface)
Temperature (Non-Operating) [°C]	-40 to 70	-40 to 70
Vibration (Operating) [m/s ²]	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)	7.35 {0.75 G} (5 to 300 Hz) 2.45 {0.25 G} (300 to 500 Hz)
Vibration (Non-Operating) [m/s ²]	29.4 {3.0 G} (5 to 500Hz)	29.4 {3.0 G} (5 to 500Hz)
Shock (Operating) [m/s ²]	686 {70 G} (2 ms duration)	686 {70 G} (2 ms duration)
Shock (Non-Operating) [m/s ²]	2,450 {250 G} (2 ms duration)	2,450 {250 G} (2 ms duration)
Acoustics Idle Mode [dB]	34	34
Physical		
Height [mm Max.]	26.1	26.1
Length [mm Max.]	147	147
Width [mm Max.]	101.85	101.85
Weight [g Max.]	755	755

TOSHIBA

Toshiba Consumer Internal Hard Drives.

A drive for every storage application.



Image does not represent actual product.

To see our full line of consumer HDD storage products, visit:

storage.toshiba.com/consumer-hdd

¹ One Terabyte (1TB) means $10^{12} = 1,000,000,000,000$ bytes using powers of 10. A computer operating system, however, reports storage capacity using powers of 2 for the definition of $1TB = 2^{40} = 1,099,511,627,776$ bytes, and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system and other factors. Actual formatted storage capacity may vary.

² CMR is Conventional Magnetic Recording technology.

³ 2.5-inch and 3.5-inch mean the form factor of HDDs. They do not indicate drive's physical size.

⁴ Number of surveillance cameras support capability is defined by performance simulation with High Definition cameras at up to 10Mbps rate, depending on the HDD model. Actual results may vary based on various factors, including the types of cameras installed, the system's hardware and software capabilities, and the video compression technology used, as well as system variables such as resolution, frames per second, and other settings. Compatibility may vary depending on user's hardware configuration and operating system. "High Definition" is calculated assuming Full HD 1080p, 30fps, transfer rate of up to 10Mbps/stream.

⁵ As for "Drive Bays Supported", please contact your Solutions Provider because the compatibility with the host device will vary based on the system.

⁶ Drive life may vary depending on usage and workload. See also MTTF/MTBF and Annual Workload Rating for more detail.

⁷ The maximum sustained data rate and interface speed may be restricted to the response speed of host system and by transmission characteristics. Read and write speed may vary depending on the host device, read and write conditions, and file size. Transfer speed varies by capacity.

⁸ MTTF (Mean Time to Failure) or MTBF (Mean Time Between Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF or MTBF. MTTF (Mean Time to Failure) or MTBF (Mean Time Between Failure) of the HDDs during its life time is 600,000 hours and AFR (Annualized Failure Rate) is 1.46%, or 1.0 million hours and AFR is 0.88%, or 1.2 million hours and AFR is 0.73%, or 2.5 million hours and AFR is 0.35% (depending on HDD models). This assumes power-on hours are 24 x 7 in normal usage (8760 h/year power on hours, up to 180TB/year, or up to 300TB/year, or up to 550TB/year total data transfers (depending on HDD models), and average HDA surface temperature: 40°C or less). Use at case HDA surface temperature above 40°C may degrade product reliability and reduce warranty period.

⁹ Annual Workload Rating: HDDs keep track of various drive usage such as power on hours, lifetime writes and lifetime reads from the host computer. With this data we calculate an Annualized Workload Rate, under 40 deg. C ambient environments, Annualized Workload Rate = (Lifetime Writes + Lifetime Reads) * (8760 / Lifetime Power On Hours) in case Power On time is 8760h or longer. Otherwise (i.e. Power On time is shorter than 8760h), Annualized Workload Rate = (Lifetime Writes + Lifetime Reads) Each drive is designed to perform up to the Annualized Workload Rate stated, after which the drive may be expected to decline. The Annualized Workload Rate in no way alters the warranty policy for such drive. Workload is defined as the amount of data written, read or verified by commands from host system.

¹⁰ Standard limited warranty applies. The warranty brochure can be viewed online at <http://storage.toshiba.com/consumer-hdd/warranty-info>.

¹¹ Operation in high surface temperature will shorten the useful life of the drive. The recommended operating surface temperature is less than 60°C.

¹² Product specifications, configurations, software, components and features are subject to change without notice.

¹³ Compatibility may vary depending on user's hardware configuration and operating system.

¹⁴ OptiFrame is a trademark or registered trademark of Toshiba Electronic Devices & Storage Corporation in the United States and other countries. All other trademarks are the property of their respective owners.

¹⁵ Product image may represent a design model.